

Lot Details 15696-267								
Assembly ID	Material ID	Short Description	Long Description	Qty	UoM	Valuation Type	Manufacturing Part Number	WbsElementDesc
CI018218	CI001184	CrossoverFlow Coupling 4.5"	Cross Over Flow Coupling, 4 1/2" 17.0# Vam Top Box x 5 1/2" 26.0# Vam Top Box, 13Cr110HP2 x 8'	1	EA	CLASS C	FCPLG-4.5-5.5-17-26-HP213CR110-VAMTOP-BB	Jack - Complete WR758 PS001
	CI001188	CrossoverFlow Coupling 4.5"	Cross Over Flow Coupling, 4 1/2" 17.0# Vam Top Box x 5 1/2" 26.0# Vam Top Box, 13Cr110HP2 x 8'	1	EA	CLASS C	FCPLG-4.5-5.5-17-26-HP213CR110-VAMTOP-BB	Jack - Complete WR758 PS001
	CI003983	Pup Joint 4.5"	Pup jt. 4 1/2" 17.0# Vam Top Box x Pin, 13Cr110HP2 x 10'	1	EA	CLASS C	PJ-4.5-17-HP213CR110-VAMTOP-BP	Jack - Complete WR758 PS001
	CI004119	Pup Joint 4.5"	Pup jt. 4 1/2" 17.0# Vam Top Box x Pin, 13Cr110HP2, 210 degree x 10'	1	EA	CLASS C	PJ-4.5-17-HP213CR110-VAMTOP-210DEG-BP	Jack - Complete WR758 PS001
	CI004166	Pup Joint 4.5"	Pup jt. 4 1/2" 17.0# Vam Top Pin x Pin, 13Cr110HP2 x 4'	1	EA	CLASS C	PJ-4.5-17-HP213CR110-VAMTOP-PP	Jack - Complete WR758 PS001
	CI018031	4-1/2 DCIN	4-1/2 DCIN	1	EA	CLASS C	1.0092295E8	Jack - Complete WR758 PS001
CI025381	CI012848	Halliburton Combination Adapter	Halliburton Combination Adapter,3 1/2-10.30 AB-HD-L Box x 3 1/2-10.20 VAMTOP Pin,4.195 in. Max OD,2.897 in. Min ID,17.05 in. Length,Super 13% Chrome Matl,110000 psi Min Yield,15890 psi Pressure Rating,Std/CO2 Service	1	EA	CLASS C	ADPTR-3.5-10.2-S13CR110-HD-L-VAMTOP-BP	TUSD PS011 Completion
	CI014851	No-Go Seal Unit Locator	No-Go Seal Unit Locator 3.88 in. Seal Bore ID-Min NO-GO Latch Type 3 1/2-10.20 VAMTOP Box-pin 4.21 in. Max OD 2.884 in. Min ID 21.85 in. Length Super 13% Chrome Matl 110000 psi Min Yield Std/CO2 Service	1	EA	CLASS C	1.01437152E8	TUSD PS011 Completion
	CI017159	ATP Premium Seal Unit	ATP Premium Seal Unit,3.88 in. Seal Bore ID-Min,3.872 in. Max OD,2.874 in. Min ID,23.11 in. Length,20 in. Make-up Length,Super 13% Chrome Matl,110000 psi Min Yield,AFLAS RUBBER/25% GLASS FILLED TEFLON/PEEK Seal Matl,3 1/2-10.20 VAMTOP-SC80 Box x 3 1/2-10.20 VAMTOP Pin,100-450 deg. F TEMPERATURE RATING,15000 psi Pressure Rating,Std/CO2 Service	1	EA	CLASS C	1.0143723E8	TUSD PS011 Completion
	CI024980	Seal Unit	SEAL UNIT,3.880,3 1/2-10.20 VAMTOP,.BBE	1	EA	CLASS C	1.02887947E8	TUSD PS011 Completion
	CI025740	Pup Joint 3.5"	PUP JOINT, 3 1/2" 10.20# SM13CRS110 AB-HDL BOX X PIN X 2' LONG	1	EA	CLASS C	PJ-3.5-10.2-SM13CRS110-HD-L-BP	TUSD PS011 Completion
CI031754	CI022644	Pup Jt - 5.5IN 26LB C110 VAMTOP (B x P)	Pup Joint, 5 1/2" 26# C110 Vam Top Coupling Box X Pin X 2' Long	1	EA	CLASS C	VAM-103-176-PIN	Big Foot-LL-Tubing (4 sets)
	CI027319	Pup Jt - 5.5IN 26LB C110 JFE LION (B x P)	CROSSOVER PUP JOINT, 5 1/2" 26# C110 VAM TOP COUPLING BOX X JFE LION SD49 PIN X 3' LONG	1	EA	CLASS C	TCM-K06190P-ACAK	Big Foot-LL-Tubing (4 sets)
CI051452	CI051517	Locator	LOCATOR, POP LOC 70-7740 BD/AFL/VI 32 ISB W/ 4" 11.6# VT BX x 3.560" -8SA PN 9.5K FW13SCr110-C	1	EA	CLASS A	403.4207F	Jack AD PS003 Completions LL
	CI051520	Unit, Seal	Unit, Seal 4.00" x 1' BD/AFL/VI 3.250" ISB w/Std Insert w/3.560" -8SA Bx x Pn 9K 13HCr	1	EA	CLASS A	403.0323C	Jack AD PS003 Completions LL
	CI051521	Unit, Seal	Unit, Seal 4.00" x 1' BD/AFL/VI 3.250" ISB w/Std Insert w/3.560" -8SA Bx x Pn 9K 13HCr	1	EA	CLASS A	403.0323C	Jack AD PS003 Completions LL
CI051461	CI051516	Locator	LOCATOR, POP LOC 70-7740 BD/AFL/VI 32 ISB W/ 4" 11.6# VT BX x 3.560" -8SA PN 9.5K FW13SCr110-C	1	EA	CLASS A	403.4207F	Jack AD PS003 Completions LL
	CI051518	Unit, Seal	Unit, Seal 4.00" x 1' BD/AFL/VI 3.250" ISB w/Std Insert w/3.560" -8SA Bx x Pn 9K 13HCr	1	EA	CLASS A	403.0323C	Jack AD PS003 Completions LL
	CI051519	Unit, Seal	Unit, Seal 4.00" x 1' BD/AFL/VI 3.250" ISB w/Std Insert w/3.560" -8SA Bx x Pn 9K 13HCr	1	EA	CLASS A	403.0323C	Jack AD PS003 Completions LL
	CI007641	EXT,HRRP UPR,5 1/4-8 STUB AC,3.88,.BBE	Gravel Pack Extension 96.94 in. Length 5 1/4-8 STUB AC Pin-pin 5.69 in. Max OD 4.57 in. Min ID Super 13% Chrome Matl 110000 psi Min Yield Std/CO2 Service	1	EA	CLASS C	101495982	Big Foot-Ph 4-LL-Spares / Excess
	CI020268	Orientated Pup Joint 3.5	TIMED PUP JOINT, 3 1/2" 10.20# T95 Vam Top Coupling Box X Pin X 3' Long @ 180 degree	1	EA	CLASS C	VAM-103-068-PIN@180	Big Foot-Ph 4-LL-Spares / Excess
	CI027849	Pup Joint	CPLD PUP JT,7-42.70 VAM21 X 240.22,.BLL	1	EA	CLASS C	PJ-7-42.7-0-VAM21-0	Jack - Future Dev - D&C LL - Completion
	CI030723	PUP JT EXT,6 5/8-32.00 AB-HD-L X 1 .BBE	Pup Joint,179.0 in. Length,6 5/8-32.00 AB-HD-L Pin-pin,6.691 in. Max OD,5.567 in. Min ID,Super 13% Chrome Matl,110000 psi Min Yield,Std/CO2 Service	1	EA	CLASS C	102303432	Big Foot-Ph 4-LL-Spares / Excess

	CI030936	CPLG,IND,6 5/8-32.00 AB-HD-L,S13CR .BBE	Halliburton Sand Control Indicator Coupling/Receptacle, 6.691 in. Max OD, 4.750 in. Min ID, 13.66 in. Length, 6 5/8-32.00 AB-HD-L Box x Box, Std/CO2 Service, 101026123 (12MPC65230-A) Mating Collet, 12P99342-BBE	1	EA	CLASS C	101396234	Big Foot-Ph 4-LL-Spares / Excess
	CI030937	PUP JT,6 5/8-32.00 AB-HD-L X 115.0 .BBE	Pup Joint,118.0 in. Length,6 5/8-32.00 AB-HD-L Pin-pin,6.691 in. Max OD,5.567 in. Min ID,Super 13% Chrome Matl,110000 psi Min Yield,Std/CO2 Service	1	EA	CLASS C	102301650	Big Foot-Ph 4-LL-Spares / Excess
	CI031752	ORIENTATED PUP JOINT 5.5	Orientated Pup Joint, 5 1/2" 26# C110 Vam Top Coupling Box X Pin X 3' Long @ 60 degree	1	EA	CLASS C	VAM-103-176-PIN@60	Big Foot-Ph 4 Drill - A6 Texas-COM
	CI031753	TIMED PUP JOINT 5.5	TIMED PUP JOINT, 5 1/2" 26# C110 JFE LION SD49 COUPLING BOX X PIN X 3' LONG @ 20 DEGREE	1	EA	CLASS C	TCM-K06190PK06190O-ACAK@20	Big Foot-Ph 4 Drill-A11 New York- COM
	CI036891	CPLG,IND,7 5/8-42.80 AB-HD-L,ALY 925.BBE	Sand Control Indicator Coupling/Receptacle, 7 5/8-42.80 AB-HD-L Box-pin, 7.701 in. Max OD, 6.01 in. Min ID, 26.45 in. Length, H2S/CO2 Service	1	EA	CLASS C	101497873	Big Foot-Ph 4-LL-Spares / Excess
	CI036927	Perma-Series Production Packer (AFLAS) - 41XX-LAS-125 6RTH-LTH-LH (B)	Special Wireline-Set Perma-Series? Production Packer 9 5/8 in. 47-53.5 and 9 7/8 in. 65.10 ppf Weight Range 4 inch Seal Bore ID-Min 8.25 in. Max OD 68.94 in. Length 41XX Low Alloy Steel Matl 125000 psi Min Yield AFLAS RUBBER Element Matl 100-450 deg. F TEMPERATURE RATING Std Service 15000 psi Pressure Rating	1	EA	CLASS C	1.02585683E8	SM - Complete Injector Well IS03
	CI038853	CPLG,IND,7 5/8-42.80 AB-HD-L,S13CR,.BBE	Halliburton Sand Control Indicator Coupling/Receptacle	1	EA	CLASS C	101437747	Big Foot-Ph 4-LL-Spares / Excess