

MANUFACTURER**M/S BHARAT WIRE ROPES LTD. CHALISGAON**

No. E-W/C-368

TEST CERTIFICATE

Date: 20.03.2023

Customer	Elite Sales
Customer Order Ref.	802718, DATE:- 22-Dec-2022
Work Order No	RLROSO/2223/09719, DATE:- 11-Jan-2023
Reel Number	BWR/9719/06/002

SPECIFICATION	
Applied Standard	RRW-410G
Nominal Diameter of Rope	44.5 MM (1 3/4 Inch)
Construction	6X36WS
Strand Construction	14-7+7-7-1
Tensile Grade of Steel Wire Rope	EEIPS
Wire Finish	GALVANIZED-B
Types of Core	IWRC
Type of Lay & Direction	RHOL
Length of Rope	3000 FT X 01 REEL
Lubrication	A4
Min Breaking Force	1500 KN
Pre Stretching	N/A

RESULTS OF TEST & EXAMINATION				
S.No.	Reel No.	Dia (mm) off Tension	Lay Length (mm) off tension	Actual Breaking Load kN
1	BWR/9719/06/002	44.84	289	1567.2

This is to Certify that the above tests have been carried out in accordance with the Specifications.

For.BHARAT WIRE ROPES LTD


Checked By
Authorised signatory

MANUFACTURER**M/S BHARAT WIRE ROPES LTD. CHALISGAON**

No. E-W/C-369

TEST CERTIFICATE

Date: 20.03.2023

Customer	Elite Sales
Customer Order Ref.	802718, DATE:- 22-Dec-2022
Work Order No	RLROSO/2223/09719, DATE:- 11-Jan-2023
Reel Number	BWR/9719/07/002 & 003

SPECIFICATION	
Applied Standard	RRW-410G
Nominal Diameter of Rope	44.5 MM (1 3/4 Inch)
Construction	6X36WS
Strand Construction	14-7+7-7-1
Tensile Grade of Steel Wire Rope	EEIPS
Wire Finish	GALVANIZED-B
Types of Core	IWRC
Type of Lay & Direction	RHOL
Length of Rope	3250 FT X 02 REEL
Lubrication	A4
Min Breaking Force	1500 KN
Pre Stretching	N/A

RESULTS OF TEST & EXAMINATION				
S.No.	Reel No.	Dia (mm) off Tension	Lay Length (mm) off tension	Actual Breaking Load kN
1	BWR/9719/07/002	44.84	289	1567.2

This is to Certify that the above tests have been carried out in accordance with the Specifications.

For.BHARAT WIRE ROPES LTD


Checked By
Authorised signatory