

Features

FEATURES OF THE 960/965 Á LA CARTE STANDARD FEATURES

- Multi drop buss capabilities (MDB).
- Extensive diagnostics capabilities.
- Friendly text-based interface.
- Dex/UCS compatible.
- Real time clock.
- Machine reset capability.
- Chime.

PRICING

- Global pricing by machine or by shelf.
- Extensive accountability, including all discounts and free vends.
- Shutdown capabilities
- Combo vends.
- Programmable spiral count.
- Upload and download capabilities for pricing and set up.
- Programmable maximum payout.

SCROLLING DISPLAY

- User friendly two-line scrolling display to help with the selection process and provide customer feedback.
- User programmable point of sale and operational messages.
- 2 line display with 20 characters on each line.

NOISE LEVEL

Operates at less than 70 db (A).

ACCEPTABLE AMBIENT OPERATING TEMPERATURE RANGE.

All equipment manufactured by Automatic Products is designed to work properly in a temperature range of 10°C to 38°C (50°F to 100°F) in still air (75% R.H. non-condensing). The machine is being stored in a temperature range of -18°C to 68°C (0°F to 155°F).

Specifications	965 Domestic	965 Export	960 Domestic	960 Export
Height	72" / 183 cm	72" / 183 cm	72" / 183 cm	72" / 183 cm
Width	10.25" / 26 cm	10.25" / 26 cm	37" / 94 cm	37" / 94 cm
Depth	33.33" / 84 cm	33.33" / 84 cm	33.33" / 84 cm	33.33" / 84 cm
Floor Space	2.37 Sq. Ft./ .22 Sq Meter	2.37 Sq. Ft./ .22 Sq Meter	8.56 Sq. Ft./ .78 Sq Meter	8.56 Sq. Ft./ .78 Sq Meter
Container Size				
Voltage (AC)	120V	230V	120V	230V
Hertz	60Hz	50Hz	60Hz	50Hz
Standby Amperes	0.7A	.35A	1.7A	.8A
Running Amperes	1A	.5A	16A	8A
Watts	120W	1440W	1920W	1840W
Refrigerant Type	N/A	N/A	404A	404A
Refrigerant Charge	N/A	N/A	23oz / 0.25 Kg	23oz / 0.25 Kg
High Side Test Pressure	N/A	N/A	440 psi	440 psi
Low Side Test Pressure	N/A	N/A	162 psi	162 psi
Shipping Weight	190 lbs / 86 kg	190 lbs / 86 kg	800 lbs / 363 kg	800 lbs / 363 kg