



Prepared By: Tracey Shiflet

Model	D8T	Job Site	--		Inspection Date	09Jan25
Manufacturer	Caterpillar		<u>Left</u>	<u>Right</u>	Next Inspection Date	22Jul31
Serial Number	FMC00706	Track Sag (4.10 in - 4.90 in)	--	--	Next Inspection Hours	11865
Reference Number	--	Frame Ext (max 6.00 in)	3.50 in	3.50 in	<u>Underfoot Conditions</u>	
Hour Meter Reading	11800	Frame Ext %	58%	58%	Impact	--
Hours Per Week	2.2	Dry Joints	--	--	Abrasion	--
Total Odometer Reading	--	Link Roller System	45%	45%	Moisture	--
Forward Odometer	--				Packing	--
Reverse Odometer	--				Bushing Allowable Wear	Greater
Distance Per Week	--				Link Allowable Wear	Greater

Position		Part Number		Status		Hours on Wear Surface		Measurement (inches)		Percent Worn		Projected Hour Meter 100%		Projected Hour Meter 120%			
Component		Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right	Left	Right		
Link Assemblies		Left: 2726009				Right: 2726009				Pitch: 8.5 in (215.9 mm)				Sections: 44			
Track Link		8E4513	8E4513	Original	Original	800	800	5.68 (D)	5.68 (D)	44%	44%	12818	12818	13182	13182		
Bushing (Ext)		6Y3914	6Y3914	Original	Original	800	800	2.84 (C)	2.86 (C)	74%	70%	12081	12143	12297	12371		
Track Shoe		Left Width: 26.00in						Right Width: 26.00in									
		3299270	3299270	Original	Original	800	800	2.50 (D)	2.50 (D)	40%	40%	13000	13000	13400	13400		
Idlers																	
Front		2441324	2441324	Original	Original	800	800	1.00 (D)	1.00 (D)	44%	44%	12818	12818	13182	13182		
Rear		2441323	2441323	Original	Original	800	800	0.98 (D)	0.98 (D)	40%	40%	13000	13000	13400	13400		
Track Roller																	
Front	S	6206380	6206380	Original	Original	800	800	1.00 (D)	1.00 (D)	45%	45%	12778	12778	13133	13133		
2	S	6206380	6206380	Original	Original	800	800	0.94 (D)	0.94 (D)	39%	39%	13051	13051	13462	13462		
3	D	6206402	6206402	Original	Original	800	800	0.94 (D)	0.94 (D)	32%	32%	13500	13500	14000	14000		
4	D	6206402	6206402	Original	Original	800	800	0.90 (D)	0.90 (D)	28%	28%	13857	13857	14429	14429		
5	D	6206402	6206402	Original	Original	800	800	0.90 (D)	0.90 (D)	28%	28%	13857	13857	14429	14429		
6	D	6206402	6206402	Original	Original	800	800	0.86 (D)	0.86 (D)	23%	23%	14478	14478	15174	15174		
7	S	6206380	6206380	Original	Original	800	800	0.86 (D)	0.86 (D)	31%	31%	13581	13581	14097	14097		
8	S	6206380	6206380	Original	Original	800	800	0.94 (D)	0.94 (D)	39%	39%	13051	13051	13462	13462		
Sprocket																	
		3145462	3145462	Original	Original	800	800	--	--	--	--	--	--	--	--		
CONDITION: Good								CONDITION: Good									



Left Sprocket



Right Sprocket

Recommendations

--

Photos

(U) Ultrasonic | (C) Caliper | (D) Depth Gauge | (T) Tape | (E) Estimated