



IP6000 Communication Software/Hardware Package, VEIP6K-1

VEIP6K-1 COMMUNICATIONS PACKAGE - LOADED WITH FEATURES!

Automated daily communication

Emergency notification

Calendar event scheduling

Graphical interface – for easy point-and-click message initiation

Privacy - Terms

Valcom IP systems can be as simple as an IP speaker accessed directly from an IP phone system or as complex as a multisite emergency mass notification system with 1000s of IP speakers, horns, LED signage, email alerts, PC screen alerts and strobes.

Most systems are accessed by Session Initiation Protocol (SIP) and/or FXO ports, have integration to a small number of analog systems or speakers, have switch inputs to activate emergency messages, and have relays to interface with access control systems or other non-Valcom systems.

Other very common features include bell schedules, prerecorded audio messages, email alerts and a GUI control/management interface.

The **IP6K Headend Package** is a perfect starting point for most systems as it provides all these most common features in a convenient 19-inch (48.26 cm) 3 rack unit* package.

Additional gateways, IP speakers, clocks and IP LED signs may be added to your Valcom system as required for your specific application.

Specifications

Resources

How to Buy

SPECIFICATIONS

Dimensions & Weight

VEIP6K-1:

Dimensions:

3.5in H x 19.0in W x 12.0in D

(8.89cm H x 48.26cm W x 30.48cm D)

Weight:

16.90lbs (7.66kg)

8/22/25, 4:19 PM

Smart UPS:

Dimensions:

1.75in H x 19.00in W x 9.00in D

 $(4.45 \text{cm} \times 48.26 \text{cm} \times 22.86 \text{cm})$

Weight:

23.75 (10.77kg)

Shipping Weight:

45.00lbs (20.25kg)

3 rack unit

It is used as a measurement of the overall height of 19-inch frame. Equipment is typically 1U, 2U or 3U in height.



© 2025 Valcom All rights reserved.

^{*}A rack unit (abbreviated U or RU) is a unit of measure defined as 1 ¾ inches (44.45 mm).