



LINE-COMMUTATED POWER CONVERTER

DATA SHEET OF POWER SECTION - CLASS2

© 2024 GE Vernova. All rights reserved.

This document and the information it contains is the property of the General Electric Company and/or its affiliates. It has been provided solely for private use. Copying, reproducing, selling, importing, exporting, displaying, transmitting or distributing this document and any of the information it contains is strictly prohibited except as expressly authorized in writing by the General Electric Company and/or its affiliates.

Project : LINE-COMMUTATED POWER CONVERTER
Document: DATA SHEET OF POWER SECTION - CLASS2
File : PowerConverter-B6C_CL2-DataSheet-401.03.docx

CLASS II (GE INTERNAL NON-CRITICAL)

Ref : B6C_CL2-401.03
Revision : 003
Date : 2024-09-23
Page : 1/3



1. POWER CONVERTER DATA SHEET – CLASS2

GENERAL CHARACTERISTICS / AMBIENT CONDITIONS	
Standards	IEC 60146-1-1 IEC 60146-2
Access	Front/Rear
Installation	indoor
Enclosure / Ingress protection	IP00
Operating temperature range	5°C – 40°C (41°F – 104°F)
Storage temperature range (without coolant)	-20°C – 65°C (-4°F – 149°F)
Storage temperature range (with coolant)	5°C – 65°C (41°F – 149°F)
Humidity	5% – 95% without condensation
Altitude	<1000 m / <3280 ft
Efficiency	>98%
Losses (rms)	83,0 kW
Aux. power (thyristor firing units)	24Vdc (120W)
Insulation: DC to ground	10 kV
INPUT DATA	
Voltage	3AC 1208 V (+/-10%)
Frequency	45 ... 63 Hz
OUTPUT DATA	
Voltage ^(*1)	DC 0 – 1794 V
Rated Current (continuous operation)	DC 16000 A
COOLING	
Cooling system ^(*2)	Water cooled (deionized water) (cooling water provided by additional cooling unit)
Water flow ^(*3)	108 l/min (28,5 gal/min)
max. inlet temperature	40°C (104 °F)
Water pressure	<6bar (< 87 psi)
DIMENSIONS WEIGHTS	
Width / Height / Depth	2200mm (7.22ft) / 2528mm (8.29ft) / 541mm (1.77ft)
Weight	955 kg (2105 lbs)
RECTIFIER STACK	
Semiconductor	Thyristor
Type	T2351N52
Number of thyristors per branch / total	6 / 24
Voltage safety factor	2,77
Current safety factor - based on load cycle for special application within project TOKAMAK SPARC	2,29
Protection fuse / type	Semiconductor fuse - One per thyristor 4SBK2100A 1500VAC (EATON)
Fuse rated voltage	AC 1500 V
Fuse rated current	2100 A
Fuse breaking current	200 kApeak
Temperature monitoring	Temp. measurement per thyristor

(*1) @no load / @110% grid voltage

(*2) deionized water – required conductivity <2µs/cm

(*3) two parallel cooling branches → 2x54l (2x14,2 gal/min) - for details see drawing D0103960

CLASS II (GE INTERNAL NON-CRITICAL)

Project : LINE-COMMUTATED POWER CONVERTER
Document: DATA SHEET OF POWER SECTION - CLASS2
File : PowerConverter-B6C_CL2-DataSheet-401.03.docx

Ref : B6C_CL2-401.03
Revision : 003
Date : 2024-09-23
Page : 2/3



THYRISTOR FIRING	
Firing device	<div>Tiny TAE (one per thyristor)</div> <ul style="list-style-type: none">- fibre optic communication with IMP-panel ^(*4)- generation of firing impulse- temperature measurement- voltage measurement- bin. input for fuse monitoring

(*4) additional IMP panel needed for data transmission between Power Converter (power section) and control equipment
(see drawing IMP-panel_GA-210.01)

Power section CLASS2 is available as “forward” and “reverse” type.

“forward”→ DC+ at the top busbar

“reverse”→ DC+ at the bottom busbar

Construction of “forward” and “reverse” type is mirror-imaged, for easy configuration of antiparallel rectifier system.

For details see drawing D0103960.