



Model: MRW030-E

All trucks shown with optional equipment. Please refer to quotation specifications.

CUSTOMER DETAILS

CUSTOMER

ADDRESS

SHIP-TO ADDRESS

CONTACT NAME

PROPOSED BY

EMAIL

clm@eastonva.hyster-yale.com

DATE

2024-01-29

QUOTE EXPIRATION

2024-02-28

Quoted: MRW030-E - 2

MRW030-E

Proposal Summary

Included Items	Description	Quantity
Model	MRW030-E	1
Construction	Key Switch Start Standard Environmental Construction +32°F to +120°F 24 Volt	
Powertrain Options	UL Classification Type "E"	
Battery Compartment	33.0" L x 13.5" W Battery Compartment Lift Out Battery Removal	
Mast	2 Stage Limited Free Lift Mast 123" Maximum Lift Height, 83" Overall Lowered Lift Height	
Carriages & Attachments	32.5" Hook Type Integral Sideshift Carriage 48" (1220mm) High Load Backrest Extension	
Forks	42" Long x 1.5" Thick x 4.0" Wide (1067mm x 38mm x 102mm) - Class II Hook Type - Standard Taper Forks	
Wheels & Tires	4" x 2.8" Tandem Polyurethane Load Wheels Drive Tires - 10 x 5 - Pressed-on Smooth Polyurethane	
Basearm	35" Inside Dimension - 43.0" Overall Width Outrigger Bars	
Operator Compartment	Battery Discharge Indicator with Hour Meter and Fault Light Factory Set for use with Lead Acid Battery Wire Mesh Screen	
Directional Control	Composite Control Handle	
Warranty	12 Months / No Hour Limit Full Truck Warranty, 36 Months / 6,000 Hours Powertrain Warranty, 60 Months / 10,000 Hour Frame Warranty; please see full Warranty Statement for additional details.	
Literature & Nameplate	English Literature Pack and Labels	
Battery & Charger Accessories	Battery Connector - Red SB® 175	
Fees & Surcharges	Freight Fees & Surcharges	