

Lot Details: 30846-7							
Material	Qty	Material Description	Plant	Plant Name	Storage Location	Desc. of Storage Loc	WBS Element
12237.A	1 EA	HANGER, CASING;TYP:BRIDGING LOCKDOWN,RTNG:1500PSI,CONN SZ:10-3/4IN ,MFR:VETCO GRAY,PN:H147448-1,MN:HC-2 MS-700	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
13547.A	4 EA	HANGER, CASING;TYP:BRIDGING LOCKDOWN,RTNG:1500PSI,CONN SZ:10-3/4IN,VETCO GRAY,EQ MODEL:HC-2 MS-700	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-1
13543.A	1 EA	HANGER, CASING;TYP:SUBSEA,CONN SZ:13- 5/8IN,CONN TYPE:VAM TOP BOX ,WT:88.20LB/FT,SPCL FEATRS:MINIMUM YIELD STRENGTH: 120 KSI,VETCO GRAY,EQ MODEL:HC-2 MS700	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
13543.A	2 EA	HANGER, CASING;TYP:SUBSEA,CONN SZ:13- 5/8IN,CONN TYPE:VAM TOP BOX ,WT:88.20LB/FT,SPCL FEATRS:MINIMUM YIELD STRENGTH: 120 KSI,VETCO GRAY,EQ MODEL:HC-2 MS700	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-1
27991.A	1 EA	HEAD;TYP:CIRCULATING,DIM:88.2 X 23- 5/8IN,MATL:STEEL AISI 4145H,SPCL FEATRS:CASING CONNECTION TYPE: FH BOX X TSH 523 PIN, CONNECTION SIZE:13-5/8 X 5-1/2 IN	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-1
31297.A	2 EA	BUSHING;OD:13-5/8IN,SPCL FEAT:MEDIA: WATER, SIZE: 6-5/8 IN, CONNECTION TYPE: FH BOX X TSH 523, WEIGHT: 88.2 LB/FT, MINIMUM YIELD STRENGTH: 120 KSI, LENGTH: 4 FT,PN:325-E135-06J	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
71010.A	1 EA	BUSHING;PN:325-E106-09C,TYP TYPE E, WATER,SZ 6- 5/8 IN,OD 10-3/4 IN,WT 65.70 lb/ft,CONN 1 TYP TSH BLUE NF PIN,CONN 2 TYP FH BOX,LG 4 ft,MATL GR	1002	JV – PRC – Ratio	0203	ISY	CP-100408-23-1
71010.A	1 EA	BUSHING;PN:325-E106-09C,TYP TYPE E, WATER,SZ 6- 5/8 IN,OD 10-3/4 IN,WT 65.70 lb/ft,CONN 1 TYP TSH BLUE NF PIN,CONN 2 TYP FH BOX,LG 4 ft,MATL GR	1002	JV – PRC – Ratio	0203	ISY	CP-100408-23-1
12158.A	7 EA	BUSHING;TYP:WEAR,SZ:13-3/8 X 13-5/8IN,OD:18- 3/4IN,MFR:VETCO GRAY ,PN:H57224-1,EQ MODEL:MS- 700	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-1
12158.A	1 EA	BUSHING;TYP:WEAR,SZ:13-3/8 X 13-5/8IN,OD:18- 3/4IN,MFR:VETCO GRAY ,PN:H57224-1,EQ MODEL:MS- 700	1002	JV – PRC – Ratio	0203	ISY	CP-100408-23-1
04279.A	32 EA	SEAL, ASSEMBLY;MATL:METAL TO METAL,APPLN:SS WELLHEAD,MFR:VETCO GRAY ,PN:H57028- 1H627,<(>,<)>EQ MODEL:MS-1	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-1
04279.A	3 EA	SEAL, ASSEMBLY;MATL:METAL TO METAL,APPLN:SS WELLHEAD,MFR:VETCO GRAY ,PN:H57028- 1H627,<(>,<)>EQ MODEL:MS-1	1002	JV – PRC – Ratio	0203	ISY	CP-100408-23-1
04279.A	1 EA	SEAL, ASSEMBLY;MATL:METAL TO METAL,APPLN:SS WELLHEAD,MFR:VETCO GRAY ,PN:H57028- 1H627,<(>,<)>EQ MODEL:MS-1	1002	JV – PRC – Ratio	0203	ISY	CP-100411-23-1
04279.A	1 EA	SEAL, ASSEMBLY;MATL:METAL TO METAL,APPLN:SS WELLHEAD,MFR:VETCO GRAY ,PN:H57028- 1H627,<(>,<)>EQ MODEL:MS-1	1002	JV – PRC – Ratio	0203	ISY	CP-100099-23-1

12299.A	1 EA	SEAL, ASSEMBLY;TYP:ANNULUS,SPCL FEAT:WORKING PRESSURE: 15000 PSI, OUTSIDE DIA: 18-3/4 IN,APPLN:EMERGENCY WELLHEAD,MFR:VETCO GRAY,PN: H57030-1,REF:SG-TPR,<(>,<)>EQ MODEL:MS-700	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
12299.A	5 EA	SEAL, ASSEMBLY;TYP:ANNULUS,SPCL FEAT:WORKING PRESSURE: 15000 PSI, OUTSIDE DIA: 18-3/4 IN,APPLN:EMERGENCY WELLHEAD,MFR:VETCO GRAY,PN: H57030-1,REF:SG-TPR,<(>,<)>EQ MODEL:MS-700	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-1
12299.A	2 EA	SEAL, ASSEMBLY;TYP:ANNULUS,SPCL FEAT:WORKING PRESSURE: 15000 PSI, OUTSIDE DIA: 18-3/4 IN,APPLN:EMERGENCY WELLHEAD,MFR:VETCO GRAY,PN: H57030-1,REF:SG-TPR,<(>,<)>EQ MODEL:MS-700	1002	JV – PRC – Ratio	0203	ISY	CP-100408-23-1
13835.A	1 EA	SEAL;;BULK,MFR:VETCO GRAY,PN:H56081-1,	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
27450.A	1 EA	SEAL;ID:12-1/2IN,OD:13-1/2IN,THK:1/2IN,SHOR HRDNSS:90,SPCL FEATRS:B, DP: 0.75 IN,MFR:VETCO GRAY,PN:H300566-1,BRAND: POLY PAK,BRAND: MOLYTHANE	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
27443.A	1 EA	SEAL;ID:12-3/4IN,OD:13-1/2IN,THK:3/8IN,SPCL FEATRS:WITH POLYMYTE SHELL AND VITON O-SPRING,MFR:VETCO GRAY,PN:201144-21,BRAND: POLY PAK	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
27442.A	3 EA	SEAL;ID:15-7/8IN,OD:16-1/2IN,THK:0.312IN,MATL:POLY PAK MOLYTHANE ,MFR:VETCO GRAY,PN:195357-72	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
13833.A	1 EA	SEAL;MATL:STEEL,MFR:VETCO GRAY,PN:H273994-4,	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
56770.A	1 EA	SEAL;MFR:VETCO GRAY,PN:195356-30,TYP POLYPAK,APPLI VETCO GRAY MS 700 TEST PLUG,MFR:VETCO GRAY,MN:327 POLYPAK	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
57642.A	2 EA	SEAL;MFR:VETCO GRAY,PN:195356-40,TYP POLYPAK,APPLI RETRIEVING TOOL	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
13852.A	2 EA	SEAL;MFR:VETCO GRAY,PN:201144-22,MFR:POLY PAK,BRAND:UNKNOWN	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107924.A	1 EA	SEAL;OEM:BAKER HUGHES,PN:195358-34,TYP DEEP POLYPAK,ID 16.5 mm,OD 17.5 mm,WD 0.5 mm,MATL MOLYTHANE,SPEC DEPTH: 0.75 MM	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107720.A	2 EA	SEAL;OEM:BAKER HUGHES,PN:201144-16,TYP EXTRNL,SPEC BRAND: POLY PAK	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107923.A	13 EA	SEAL;OEM:BAKER HUGHES,PN:201144-6,TYP POLYPAK,ID 12.858 mm,OD 13.358 mm ,SPEC CROSS SECTION SIZE: 0.25 MM, POLYMYTE SHELL AND VITON O-SPRING	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
71858.A	2 EA	ASSEMBLY;TYP BURST DISK SUB,SZ 16 IN,DIM LG 4 ft,MATL N/A,COMPRISING CONSISTING OF (2) 20 FT X 16 IN 97#HCQ125 TSH 511 BXP PUP JOINTS, (1) 16 IN HUNTING APRS (BURST DISK SUB, (1) 20 FT 16 IN 97# TN125HC PUP JOINT ON EACH END	1002	JV – PRC – Ratio	0203	ISY	CP-100408-23-1

27445.A	2 EA	BLOCK;TYP:POSITION INDICATION IMPRESSION,APPLN:SS WELLHEAD (SIZE: 16-3/4 IN),MFR:VETCO GRAY,PN:H58650-1,EQ MODEL:MS-700	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107930.A	1 EA	DISC, RUPTURE;OEM:BAKER HUGHES,PN:H300720- 11,SPEC ASSY	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
69839.A	2 EA	DISC, RUPTURE;TYP EXTERNAL PRESSURE RUPTURE DISK (EPRD),DIA ROUND,OPRTG PRESS 7200 PSI MIN BACKPRESSURE,MATL STAINLESS STEEL,BST PRESS 2100 PSI AT 200 DEGREE F,SEAT ANGL 0,SPEC A06240- 08	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-2
12250.A	1 EA	INDICATOR;TYP:SLOPE,RANGE:0-2DEG,DISPLAY TYP:BULLSEYE,MNTG FCLTY:LEVEL INDICATOR MOUNITNG BRACKET,COMPRISING:PLASTIC HOUSING,MFR:VETCO GRAY ,PN:H57720-101	1002	JV – PRC – Ratio	0203	ISY	CP-100099-23-1
12250.A	1 EA	INDICATOR;TYP:SLOPE,RANGE:0-2DEG,DISPLAY TYP:BULLSEYE,MNTG FCLTY:LEVEL INDICATOR MOUNITNG BRACKET,COMPRISING:PLASTIC HOUSING,MFR:VETCO GRAY ,PN:H57720-101	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-1
29826.A	1 EA	INDICATOR;TYP:SLOPE,RANGE:0-2DEG,DISPLAY TYP:BULLSEYE,MNTG FCLTY:NO BRACKETS,COMPRISING:PLASTIC HOUSING,MFR:VETCO GRAY,PN:A301477-1	1002	JV – PRC – Ratio	0203	ISY	CP-100405-21-1
57656.A	4 EA	INSERT;MFR:VETCO GRAY,PN:H50228-3,TYP LEAD,APPLI MILL/FLUSH TOOLS MS 700 SPARES	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
13855.A	3 EA	KEY,ANTI ROTATION,VETCO GRAY,H57068-2	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
35926.A	40 EA	KEY;TYP:ANTI ROTATION,APPLN:36 IN, HC100/D90 CONNECTION, HORIZONTAL ,MFR:DRIL- QUIP,PN:222320,	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
63389.A	2 EA	KIT, TEST;MFR:WEATHERFORD, PN:1957846, MFR:WEATHERFORD, TYPE:ISO TRAP SAMPLER	1002	JV – PRC – Ratio	0203	ISY	CP-100042-21-1
46042.A	11 EA	O RING SET;TYP:REPLACEMENT SET,COMPRISING:TOP AND BOTTOM SEALS ,APPLI:TENARIS 16 IN, TSH 511 BOX THREAD PROTECTORS	1002	JV – PRC – Ratio	0203	ISY	CP-100045-23-1
46040.A	15 EA	O RING SET;TYP:REPLACEMENT,COMPRISING:TOP AND BOTTOM SEALS,:TENARIS 9-7/8 IN, TSH 523 BOX THREAD PROTECTORS	1002	JV – PRC – Ratio	0203	ISY	CP-100045-23-1
46043.A	11 EA	O RING SET;TYP:REPLACEMENT,COMPRISING:TOP AND BOTTOM SEALS,APPLI:TENARIS 18 IN, TSH 511 BOX THREAD PROTECTORS	1002	JV – PRC – Ratio	0203	ISY	CP-100045-23-1
13233.A	1 EA	O RING;INDUS STD:325,MATL:NITRILE,ID:1.457IN,WD:0.21IN,SHOR HRDNSS:70 DUROMETER,MFR:VETCO GRAY,PN:195000-325	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
13824.A	20 EA	O RING;INDUS STD:439,ID:6-1/2IN,WD:1/4IN,MFR:VETCO GRAY,PN:201742-439	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
93624.A	224 EA	O RING;MFR:DRIL-QUIP,PN:917155-292,MATL NITRILE	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
55784.A	2 EA	O RING;MFR:VETCOGRAY,PN:195003-361,APPLI ISOLATION TEST TOOL	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1

55791.A	6 EA	O RING;MFR:VETCOGRAY,PN:195003-454,MATL NITRILE,ID 12.475 IN,WD 0.275 IN ,SHOR HRDNSS 90 DURO,APPLI PRESSURE ASSISTED DRILL PIPE RUNNING TOOL	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107931.A	5 EA	O RING;OEM:BAKER HUGHES,PN:195000-151,INDUS STD AS568A-151,MATL NITRL,ID 2.987 IN,WD 0.103 IN,SHOR HRDNSS 70 DURO	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107721.A	4 EA	O RING;OEM:BAKER HUGHES,PN:195000-328,TYP O/T,APPLI SHEAR ASSEMBLY	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107929.A	2 EA	O RING;OEM:BAKER HUGHES,PN:195000-339,INDUS STD AS568A-339,MATL NITRL,ID 3.225 mm,WD 0.21 mm,SHOR HRDNSS 70 DURO	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
26071.A	6 EA	O RING;SPCL FEAT:CONNECTION TYPE: HC100MT,APPLI:DRIL-QUIP CONNECTOR (SIZE: 36 IN),PN:917155-411	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
27454.A	10 EA	ORING; TYP: SPECIAL, MATL:NITRILE , ID:35.812IN, WD:1/2IN, SHOR HRDNSS:70 DUROMETER,MFR:VETCO GRAY,PN:02041001	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
27440.A	4 EA	O RING;TYP:SPLICED AND VULCANIZED,INDUS STD:152,MATL:NBR,ID:30-1/2IN ,WD:0.275IN,SHOR HRDNSS:70 DUROMETER,MFR:VETCO GRAY,PN:200008-152	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
13236.A	6 EA	PIN, SHEAR;DIA:16IN,LG:18-3/4IN,APPLN:PACKOFF,MN:MS-700,MFR:VETCO GRAY ,REF:H50321-4	1002	JV – PRC – Ratio	0203	ISY	AB-100008-11-1
13236.A	12 EA	PIN, SHEAR;DIA:16IN,LG:18-3/4IN,APPLN:PACKOFF,MN:MS-700,MFR:VETCO GRAY ,REF:H50321-4	1002	JV – PRC – Ratio	0203	ISY	CP-100094-21-1
78108.A	2 EA	PIN, SHEAR;MFR:GE OIL <(>&<)> GAS,PN:H56625-7,APPLI LEAD IMPRESSION TOOL	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107925.A	4 EA	PIN, SPRING;OEM:BAKER HUGHES,PN:6701008810,MATL SS,DIA 0.25 mm,LG 1.75 mm	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
19384.A	2 EA	PLUG, BULL;TYP:ROUND,NOM SZ:3-1/2IN,CONN TYPE:8 RD,LG:4000mm ,MATL:FIBERGLASS,PN:FBP4035,MFR:STAR FIBERGLASS,BRAND:UNKNOWN	1002	JV – PRC – Ratio	0203	ISY	AB-100008-11-1
19385.A	2 EA	PLUG, BULL;TYP:ROUND,NOM SZ:5-1/2IN,CONN TYPE:8 RD,LG:4000mm ,MATL:FIBERGLASS,PN:FBP4055,MFR:SMITH FIBERCAST,BRAND:UNKNOWN	1002	JV – PRC – Ratio	0203	ISY	AB-100008-11-1
13832.A	11 EA	RING;TYP:D,MFR: VETCO GRAY,MN:H56014-1	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
13832.A	4 EA	RING;TYP:D,MFR: VETCO GRAY,MN:H56014-1	1002	JV – PRC – Ratio	0203	ISY	CP-100408-23-1
13856.A	4 EA	SCREW, CAP;MFR:VETCO GRAY,PN:195092-1,	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
55783.A	8 EA	SCREW, CAP;MFR:VETCOGRAY,PN:195008-89,APPLI PRESSURE ASSISTED DRILL PIPE RUNNING TOOL	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
107926.A	4 EA	SCREW, CAP;OEM:BAKER HUGHES,PN:A301046-63,HEAD SCKT,DIA 0.312 IN,THD PITCH: 18 TPI, SERIES: UNRC,LG 0.625 IN,CL 3A,MATL SS,MATL GR L7	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1

35928.A	44 EA	SCREW;HEAD:SOCKET,DIA:1/2IN,LG:7/8IN,MATL:ALLOY STEEL ASTM A574,THD:UNC 13TPI,CONN TYP:HC100/D90 CONNECTION,APPLI:HORIZONTAL, ANTI ROTATION KEY(SIZE: 36 IN),MFR:DRIL-QUIP,PN:917126-146	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
18860.A	11 EA	SEALANT;TYP:THREAD,MATL:NON-METALLIC TEFLON BASED,APPLI:NOV FIBERGLASS SYSTEMS API 8 RD CONNECTIONS,MFR: NOV,BRAND: STARTECH	1002	JV – PRC – Ratio	0203	ISY	AB-100008-11-1
88195.A	2 EA	SOCKET;TYP ROPE,COMM SZ 5/16 IN,MATL CARBON STEEL,APPLI E-LINE	1002	JV – PRC – Ratio	0203	ISY	CP-100042-31-1
19383.A	3 EA	TEE, PIPE;NOM PIPE SZ:3-1/2IN,CONN TYP:8 RD,MATL:FIBER GLASS,OPER PRESS:CL 1500,MFR:NOV,BRAND:FTE2035	1002	JV – PRC – Ratio	0203	ISY	AB-100008-11-1
13827.A	2 EA	TOOL, DOWN HOLE;TYP:LEAD IMPRESSION BLOCK,MFR:VETCO GRAY,PN:H190016-29	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
73545.A	1 EA	TOOL;MFR:DRIL-QUIP,PN:222671,TYP VERTICAL ANTI-ROTATION KEY REMOVAL,SZ 20,30 IN,APPLI MULTI-THREAD CONNECTORS	1002	JV – PRC – Ratio	0203	ISY	CP-100099-23-1
73545.A	1 EA	TOOL;MFR:DRIL-QUIP,PN:222671,TYP VERTICAL ANTI-ROTATION KEY REMOVAL,SZ 20,30 IN,APPLI MULTI-THREAD CONNECTORS	1002	JV – PRC – Ratio	0203	ISY	CP-100408-23-1
80453.A	2 EA	TOOL;MFR:HALLIBURTON,PN:725-30-01,TYP CEMENT SUPPORT,STYL W/ ATTACHED DART,DIA 2.5 IN,APPLI FOR USE IN 7.5 TO 20 IN DIA HOLES AND FOR USE ON 2.5 TO 6.00 IN ID DRILL PIPE	1002	JV – PRC – Ratio	0203	ISY	CP-100099-23-1
13231.A	12 EA	TOOL;MFR:VETCO GRAY,PN:04824101,TYP LEAD CONE IMPRESSION SSPE	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
27451.A	1 EA	TOOL;TYP:ISOLATION TEST,SZ:18-3/4IN,SPCL FEATRS:SEAL ELEMENT, WITH CABLE INSERTS AND SPRING REINFORCEDCORNERS,MFR:VETCO GRAY,PN:H58066-1,<(>,<)>EQ MODEL:MS-700	1002	JV – PRC – Ratio	0203	ISY	CP-100066-23-1
35964.A	2 EA	VALVE, GLOBE;SZ:2IN,CONN TYPE:FLANGED RTJ,DSGN RTNG:3170PSI,CL:1500,BDY MATL:CS,MATL GR:WCB,TRIM:SS 316,SFTGDS:SEAL GRAPHITE,TEMP RNGE:400DEG F ,APPLI:SEA WATER EII,PN:P100467,	1002	JV – PRC – Ratio	0203	ISY	CP-100097-23-1
15168.A	1 EA	AMMETER;PN:0308002,MFR:VALEPORT,MN:308	1002	JV – PRC – Ratio	0203	LIRU 7169721	AB-100008-11-1
15168.A	1 EA	AMMETER;PN:0308002,MFR:VALEPORT,MN:308	1002	JV – PRC – Ratio	0203	LIRU 7169721	AB-100008-11-1
36531.A	10 EA	DEVICE;MFR:WEATHERFORD,PN:1957850,TYP ISOTRAP,SPCL FEAT CONVERSION OF HYDROGEN SULFIDE TO A NON-HAZARDOUS MATERIAL,APPLN SHIPPING AND SUBSEQUENT ANALYSIS,BRAND:,BRAND:ISOTEC	1002	JV – PRC – Ratio	0203	SCC-A05-05	CP-100042-21-1
85921.A	1 EA	DRUM;MFR:BAKER HUGHES,PN:SDF-68-32-38-3,TYP EMPTY CORRUGATED,DIM FLANGE OD 68 IN, MAX WIDTH: 38 IN,MATL CS,SPEC ARBOR HOLE: 3.4 IN; CORE OD: 32 IN; TRAVERSE: 32 IN	1002	JV – PRC – Ratio	0203	FLOOR	CP-100042-31-1