

Lot Details: 30846-9							
Material	Qty	Material Description	Plant	Plant Name	Storage Location	Desc. of Storage Loc	WBS Element
15247.A	1 EA	PUP JOINT, CASING;NOM SZ:6-5/8IN,WT:24.00lb/ft,MATL GR:L80,TOP CONN TYP:SLHT,BOT CONN TYP:BOX X PIN,LG:10ft	1003	JV – PRC – Yam	0203	ISY	CP-100109-11-1
15245.A	1 EA	PUP JOINT, CASING;NOM SZ:6-5/8IN,WT:24.00lb/ft,MATL GR:L80,TOP CONN TYP:SLHT,BOT CONN TYP:BOX X PIN,LG:6ft	1003	JV – PRC – Yam	0203	ISY	CP-100108-11-1
15245.A	1 EA	PUP JOINT, CASING;NOM SZ:6-5/8IN,WT:24.00lb/ft,MATL GR:L80,TOP CONN TYP:SLHT,BOT CONN TYP:BOX X PIN,LG:6ft	1003	JV – PRC – Yam	0203	ISY	CP-100109-11-1
15246.A	1 EA	PUP JOINT, CASING;NOM SZ:6-5/8IN,WT:24.00lb/ft,MATL GR:L80,TOP CONN TYP:SLHT,BOT CONN TYP:BOX X PIN,LG:8ft	1003	JV – PRC – Yam	0203	ISY	CP-100108-11-1
15246.A	1 EA	PUP JOINT, CASING;NOM SZ:6-5/8IN,WT:24.00lb/ft,MATL GR:L80,TOP CONN TYP:SLHT,BOT CONN TYP:BOX X PIN,LG:8ft	1003	JV – PRC – Yam	0203	ISY	CP-100109-11-1
18865.A	1 EA	SUB;TYP:SAVER DOUBLE PIN,MATL GR:4140/4145 HT,CONN SZ:7-5/8IN,CONN TYPE:REG PIN,SPCL FEATRS:W/ API RELIEF GROOVE X GPDS-55 PIN, SIZE: OD 9-5/8 X ID 3-13/16 IN, 5-5/8 IN SHOULDER/SOULDER, MINIMUM YIELD STRENGTH: 120 KSI, QUALITY PLAN,NOBLE	1003	JV – PRC – Yam	0203	ISY	CP-100110-11-1
18864.A	2 EA	CROSSOVER, CASING;TOP CONN SZ:7IN,TOP CONN WT:29.00lb/ft, TOP CONN TYP:TSH 563 BOX,BOT CONN SZ:6-5/8IN,BOT CONN TYP:FH PIN,LG:3.125ft,MATL SPEC:AISI 4145,BASE MATL:AS	1003	JV – PRC – Yam	0203	ISY	CP-100111-11-1
12250.A	2 EA	INDICATOR;TYP:SLOPE,RANGE:0-2DEG,DISPLAY TYP:BULLSEYE,MNTG FCLTY:LEVEL INDICATOR MOUNITNG BRACKET,COMPRISING:PLASTIC HOUSING,MFR:VETCO GRAY ,PN:H57720-101	1003	JV – PRC – Yam	0203	ISY	CP-100093-11-1
13420.A	1 EA	MANDREL;TYP:OTIS LOCK,DIM:OD 3.65IN,SPCL FEATRS:WITH TOP NO-GO, 3.562 IN, 9CR-1MO MAT TEFLON/Ryton SEAL MATL, 2- 5/8-12 SLB BOTTOM THREAD, H2S SERVICE, MATERIAL NO. 101009132,PN:1 ORPT35656,	1003	JV – PRC – Yam	0203	ISY	CP-100108-11-1
13420.A	1 EA	MANDREL;TYP:OTIS LOCK,DIM:OD 3.65IN,SPCL FEATRS:WITH TOP NO-GO, 3.562 IN, 9CR-1MO MAT TEFLON/Ryton SEAL MATL, 2- 5/8-12 SLB BOTTOM THREAD, H2S SERVICE, MATERIAL NO. 101009132,PN:1 ORPT35656,	1003	JV – PRC – Yam	0203	ISY	CP-100109-11-1
13423.A	1 EA	PLUG;TYP:PRONG,SZ:3.562,APPLI:OTIS EQUALIZING RPT,SPCL FEAT:9CR-1MO MAIL, VEE-PACKING SEAL MALL, MAX OD: 3.55 IN, LENGTH: 54.7 IN, 2-5/8-12 OTIS SLB-RPT BOX, H2S SERVICE, MATERIAL NO. 120057390,PN:24RPT35665,	1003	JV – PRC – Yam	0203	ISY	CP-100108-11-1
13423.A	1 EA	PLUG;TYP:PRONG,SZ:3.562,APPLI:OTIS EQUALIZING RPT,SPCL FEAT:9CR-1MO MAIL, VEE-PACKING SEAL MALL, MAX OD: 3.55 IN, LENGTH: 54.7 IN, 2-5/8-12 OTIS SLB-RPT BOX, H2S SERVICE, MATERIAL NO. 120057390,PN:24RPT35665,	1003	JV – PRC – Yam	0203	ISY	CP-100109-11-1
15247.A	1 EA	PUP JOINT, CASING;NOM SZ:6-5/8IN,WT:24.00lb/ft,MATL GR:L80,TOP CONN TYP:SLHT,BOT CONN TYP:BOX X PIN,LG:10ft	1003	JV – PRC – Yam	0203	ISY	CP-100108-11-1

13430.A	1 EA	TOOL, WIRELINE;TYP:RUNNING,SPCL FEAT:HALLIBURTON NON-SELECTIVE: 3-1/8 IN, 3.09 IN, OD NO-GO 26.36 IN LONG, MATERIAL: ALLOY. STD/H2S, TOP THREAD: 1-1/16-10 UNS, BOTTOM THREAD: 1-3/8 IN-12UNF, FISH NECK, SIZE: 2.313 IN	1003	JV – PRC – Yam	0203	ISY	CP-100108-11-1
13430.A	1 EA	TOOL, WIRELINE;TYP:RUNNING,SPCL FEAT:HALLIBURTON NON-SELECTIVE: 3-1/8 IN, 3.09 IN, OD NO-GO 26.36 IN LONG, MATERIAL: ALLOY. STD/H2S, TOP THREAD: 1-1/16-10 UNS, BOTTOM THREAD: 1-3/8 IN-12UNF, FISH NECK, SIZE: 2.313 IN	1003	JV – PRC – Yam	0203	ISY	CP-100109-11-1
13434.A	1 EA	TOOL, WIRELINE;TYP:SB PULLING, SHEAR DOWN,SZ:3IN,SPCL FEAT:MATERIAL: ALLOY, STD SERVICE, MAX OD 2.734 X LG 17-1/2 IN, 1- 1/16 IN 10 UNS TOP THREAD,APPLI:, 5/8 IN 11UNC BOTTOM THREAD, 2.313 IN OD FISH NECK, 2.313 IN WILL ENGAGE,PN:40SB9	1003	JV – PRC – Yam	0203	ISY	CP-100108-11-1
13432.A	1 EA	TOOL;TYP:TEST,SZ:3.562IN,MATL:9 PCT CHROMIUM/1 PCT MOLYBDENUM,APPLN:RPT, H2S,MFR: HALLIBURTON	1003	JV – PRC – Yam	0203	ISY	CP-100108-11-1