



THE G. W. VAN KEPPEL COMPANY

2218 Industrial Park RD, Van Buren, AR 72956 Phone: 479-474-5281 Fax: 479-474-6048

CEMEN TECH M30 / FREIGHTLINER CHASSIS

360° SWIVEL CHUTE

- 360° SWIVEL CHUTE WITH 24" SHORT CHUTE. ACCEPTS STANDARD MIDDLE AND END CHUTES.

6 YARD PACKAGE

- INCLUDES 6 YARD BIN, 65 CUBIC FOOT CEMENT BIN AND 430 GALLON WATER TANK

ACCU-PRINTER II (AP2)

- ADVANCED SECOND-GENERATION ELECTRONIC TICKET PRINTER THAT EXPANDS THE CAPABILITIES OF THE ORIGINAL ACCUPRINTER. TOUCHSCREEN DISPLAY ALONG WITH THE ABILITY TO STORE MORE MIX DESIGNS AS WELL AS UPLOAD MIX DESIGNS AND DOWN LOAD MIX DATA THROUGH USB PORT. INCLUDES WATER RECORDING METER AND TICKET PRINTER.

ALUMINUM CHUTES

- TWO ALUMINUM CHUTES IN LIEU OF STANDARD CHUTES. INCLUDES BRACKET TO STORE CHUTES WHILE NOT IN USE.

CALIBRATION KIT (1/4 YARD)

- 1/4 YARD ALUMINUM, COLLAPSIBLE YIELD BOX WITH DIGITAL SCALE AND MEASURING CUPS TO AID IN CALIBRATION OF THE UNIT.

FIBER CHOPPER

- FIBER CHOPPER CUTS, PROPORTIONS, AND DISPENSES HIGH STRENGTH AR GLASS FIBER. DISPENSING RATE UP TO 18 OZ. OF FIBER PER MINUTE.

HYDRAULIC OIL COOLER-AIR

- FAN OIL COOLER TO LOWER HYDRAULIC OIL TEMPERATURE FOR OPERATION IN HIGH AMBIENT HEAT CONDITIONS, EXTENDED OPERATION, OR WHEN MIX WATER CAN NOT BE USED. 1

MIXER DIAPER

- MIXER DIAPER UNDER MIXING THROAT TO CATCH MATERIALS AND PREVENT THEM FROM SPILLING. STANDARD COLOR IS YELLOW.

NIGHT OPERATING LIGHTS (LED) - QTY 5

- NIGHT OPERATING LIGHTS ALLOW SAFE OPERATION OF THE UNIT AFTER DARK. INCLUDES 5 LED TYPE FLOOD LIGHTS. ON/OFF SWITCH WILL BE LOCATED IN THE CONTROL PANEL.

SPRAY ON AGGREGATE BIN LINER

- SPRAY ON HEAVY DUTY TWO COMPONENT MODIFIED POLYUREA PROTECTIVE COATING. PROTECTS AND SEALS AGGREGATE BIN TO ADD WEARD LIFE AND PREVENTS CORROSION. 1

TARP - BLACK MESH

- ELECTRIC MOTOR OPERATED MESH TARP TO HELP SECURE YOUR AGGREGATES DURING TRANSIT. SWITCH WILL BE MOUNTED ON THE BIN SUPPORT.

STROBE LIGHTS - ONE FRONT & ONE REAR

- ONE FRONT AND ONE REAR MOUNTED STROBE CAUTION LIGHT. STROBE WILL BE MOUNTED ON THE BACK OF THE UNIT ON THE DRIVER'S SIDE, AND ON THE FRONT WATER TANK CAGE. SWITCH LOCATION WILL BE LOCATED IN THE CAB IF THE UNIT IS MOUNTED ON A TRUCK CHASSIS. THE SWITCH WILL BE LOCATED IN THE MIXER CONTROL PANEL IF THE UNIT IS MOUNTED ON A TRAILER.

THIRD ADMIXTURE SYSTEM (HIGH RANGE)

- USED FOR ADMIXES THAT REQUIRE 5 OUNCES OR MORE ADDITION RATE PER 100 LBS OF CEMENT. THE ADMIX MUST BE DILUTED TO ACHIEVE PROPER CONSISTENCY AND FLOW RATE THROUGH THE FLOW METER. SYSTEM INCLUDES A 35 GALLON (132 LITER) POLY TANK, ELECTRIC PUMP AND MECHANICAL FLOW METER WITH BUILT IN ADJUSTABLE SETTINGS.

TRANSMISSION INTEGRATION - AUTOMATIC (INCLUDES ROLL AND POUR CAPABILITY)

- TRANSMISSION INTEGRATION - AUTOMATIC (INCLUDES ROLL AND POUR CAPABILITY) 1 WIRELESS REMOTE CONTROL
- FULL FUNCTION WIRELESS REMOTE CONTROL TO OPERATE THE UNIT INDEPENDENT FROM THE CONTROL PANEL. INCLUDES E-STOP BUTTON IN CONTROL PANEL

WATER FILL PIPE WITH AIR GAP

- PREVENT WATER BACK FLOW WHEN FILLING. INCLUDES STRAINER AND CHECK VALVE. NOT OFFERED ON INSULATED WATER TANK

VIBRATORS - STONE SIDE

- STONE SIDE VIBRATORS ENSURE FLOW OF FINE MATERIALS AND SMALLER STONE SHOULD THEY BE REQUIRED FOR SPECIAL MIX DESIGNS. COMMONLY USED IN FLOWABLE FILL AND LATEX APPLICATIONS

TRUCK SECTION:

MOUNTING – CEMEN TECH INCORPORATED SUPPLIED TRUCK

CEMEN TECH PROVIDED CHASSIS. PROVIDE QUALITY WORKMANSHIP AND PROPERLY MOUNT UNIT TO APPROPRIATE CHASSIS.

TRUCK PURCHASE 1 111862.00

2024 FREIGHTLINER

- M2-106 CUMMINS L9 350HP ALLSION 3000RDS AUTO TRANSMISSION 135CT NO PUSHER

