

TOWN UNIT # 125233-16

RECEIVED FROM NEXGEN MUNICIPAL OCTOBER 27, 2016 NO APPARENT DAMAGES 146.3 KM

TOWN UNIT #: 125233-16 ASSET #: 189193

2016 MODEL YEAR FORD MODEL F-550 XL 4X2 LICENSE: AP 76983 **VIN: 1FDUF5GT1GED05464**

FITTED WITH 2016 MODEL YEAR WAYNE MODEL QUANTUM 6, 6 CU.YD.

REAR LOAD PACKER S/N: 19129

GVWR: 8,845 KG. GAWR FRONT/REAR: 2,948 / 6,671 KG. GCWR: 11,793 KG. **RGW: 8,850**

PREFERRED EQUIPMENT GROUP 960A & POWER EQUIPMENT GROUP P/W, P/L, P/HM,

TELESCOPING TRAILER TOWING MIRRORS

165 " WHEEL BASE, 84 " C/A, 47.6 " A/F

6.7 LITER DIESEL 300 HP @ 2,800, 660 LBS. FT. TORQUE @ 1,600 RPM

4.88 RATIO LIMITED SLIP REAR AXLE

150 LITERS DIESEL FUEL (MID-SHIP FITTED), 27 LITERS DEF BIODIESEL CAPABLE TO B20

EXHAUST OUTLET FITTED STREETSIDE WITH DEFLECTOR SHIELD

BLOCK HEATER

6-SPEED ELECTRONIC AUTOMATIC TRANSMISSION WITH PTO

FRONT TIRES 225/70R 19.5 128/126 N

REAR TIRES 225/70R 19.5 128/126 N

19.5 X 6.0RW RIMS 95/655 FRONT, 110/760 REAR

TRAILER ANTI-SWAY PACKAGE

TOW HOOKS

GRAB HANDLES DRIVER & PASSENGER

HEADLINER, DOME & DUAL MAP LIGHTS, FRONT POWER POINT

UPFITTER SWITCHES (4)

4-WHEEL ABS DISC

MF BATTERY DUAL 750 CCA

HD ALTERNATOR 200 AMP

HD SHOCKS, STABILIZER BARS FRONT & REAR

POWER STEERING

7-WIRE TOW HARNESS

AIRBAGS DRIVER & PASSENGER WITH PASSENGER DEACTIVATE

PASSIVE ANTI-THEFT

SOS POST CRASH ALERT

ADJUSTABLE SAFETY BELTS

PTC SUPPLEMENTAL HEATER

PAYLOAD UPGRADE 19,500 LBS. PACKAGE

TIRE PRESSURE MONITORING NOT FITTED

AM/FM/CD CLOCK RADIO AUX. AUDIO INPUT JACK

VINYL 40/20/40 SEATS

DOOR POCKETS

SYNC VOICE ACTIVATED SYSTEM

AIR CONDITIIONING

RUNNING BOARDS - DEALER INSTALLED - KENNEDY FORD

KROWN RUSTPROOFING DEALER INSTALLED - KENNEDY FORD

PAINTED OXFORD WHITE WITH CHARCOAL GRAY VINYL

PACKER UNIT S/N: 19129

UNIT IS COMPLIANT TO MANDATORY ANSI Z 245.1-1984 AND ONTARIO MOL STANDARDS FOR 1 & 2 MAN OPERATIONS.

OVERALL LENGTH 158 "

HEIGHT ABOVE CHASSIS RAIL: 62 " TAILGATE RAISED 110 "

EXTERIOR BODY WIDTH 83 “
BELOW FRAME HOPPER BOTTOM 11 “
HOPPER DEPTH 13 “
HOPPER OPENING HEIGHT 45 “
HOPPER OPENING WIDTH 70 “
HOPPER LOADING SILL 3 ½” BELOW TOP OF PACKER RAIL
HOPPER VOLUMETRIC CAPACITY 1 CU. YD.
LOWER HOPPER 7 GAUGE BOTTOM 3/16” 100,000 PSI
HOPPER WEIGHT 1,000 LBS.
C/G BODY ONLY 77 “ FROM FRONT OF BODY
C/G PAYLOAD 62 “ FROM FRONT OF BODY
BODY/FLOOR/ROOF 11 GAUGE GR 50 STEEL
BODY WEIGHT 5,520 LBS.
COMPACTION RATE 800 LBS. CU.YD.
PACKING FORCE APPLICATION 40,000 LBS.
PACKING CYCLE 13 SECONDS
HOPPER INSPECTION WITH SENSOR INTERLOCK
CURBSIDE MOUNTED TOOL RACKS @ OF THREE SLOTS
SWEEP PANEL ROTATION 100 DEGREES
TAILGATE SAFETY PROP AND TWO LIFT EYES
SAFETY GRAB HANDLES BOTH REAR SIDES WITH STEPS COMPLIANT TO ANSI
TRANSMISSION PTO 22 GPM @ 2,700 PSI @ 1,300 RPM CHELSEA 249 SERIES
PTO / PARKING BRAKE “ON” INTERLOCK SYSTEM
PTO ENGAGED WARNING LIGHT
20 USG HYDRAULIC RESERVOIR
MOL COMPLIANT INTERLOCK BUTTON BESIDE TWIN DETENT LEVERS CURBSIDE
TAILGATE LIFT/LOWER, PANEL EJECTOR CONTROLS STREETSIDE AT DRIVER FRONT
AUTOMATIC ACCELERATOR SWITCH AT TAILGATE LIFT / EJECTOR PANEL CONTROLS WITH
AUTOMATIC RETURN TO IDLE AFTER CYCLING
LED LIGHTING
UPPER LIGHT BAR: (2) 4” STOP/TAIL/TURN AND 2” DIAMETER CLEARANCE SIDE MARKER
LIGHTS
DRIVER ALERT BUZZER AT TAILGATE PANEL CONTROL HANDLES
BBS TEK BBS 102 BACK UP ALARM
AMBER STROBES WITH GUARDS FRONT & REAR OF BODY SWS 23815
TWO GRILLE MOUNTED WHELEN 900 5” X 7” AMBER STROBES
TWO REAR FLOODLIGHTS SINGLE IN CAB SWITCH GROTE TRILLIANT 36 P/E: 63871-5
REAR MUDFLAPS FORE AND AFT