TOWN UNIT # 125113-13

RECEIVED FROM PARKWAY FORD 2013 NOV. 7, 2013 157.0 KM NO DAMAGES

LICENSE: AE 90860 VIN: 1FD0W4GTXEEA24107

GVWR: 7,484 KG. GAWR: 2,722/5,443 RGW: 10,000 KG. GCWR: 13,608 KG.

RUNNING BOARDS

REMOTE KEYLESS

BARN DOOR TAILGATE

DUAL STROBES

TARPAULIN ASSEMBLY

FRAME MOUNTED TOOLBOX

VIBRATORY SHAKER

BODY FRONT TOOLBOX

FORD F-450 XL HD CREW CAB 176" WHEELBASE,

WITH 9' ELOQUIP ALUMINUM DUMP BODY S/N: AAL 12125

FRONT TIRES: 225/70R 19.5G 128/126N REAR TIRES: 225/70R 19.5G 128/126N

ALL RIMS: 19.5 X 6.0 RW FRONT PRESSURE: 85 PSI / 585 KPA REAR PRESSURE: 90 PSI / 620 KPA

SINGLE FUEL TANK: 145 LITERS

4.30 RATIO LIMITED SLIP DIFFERENTIAL

FRONT TOW HOOKS

GRAB HANDLES FRONT DRIVER & PASSENGER

FULL HEADLINER

DUAL DOME/MAP LIGHTS

DUAL 12 VDC POWERPOINTS

4 UPFITTER SWITCHES

4 WHEEL ABS POWER DISC BRAKES

BLOCK HEATER

HD SHOCKS, STABILIZER BARS FRONT & REAR

AIRBAGS DRIVER & PASSENGER

PASSIVE ANTI-THEFT SYSTEM

ADJUSTABLE SAFETY BELTS

SOS POST CRASH ALERT SYSTEM

OPTIONAL EQUIPMENT CODE #: 10A1-001CC120020W4G

PREFERRED EQUIPMENT PACKAGE: PKG. 950A

F	NG	INI	F	П	ıcı	-C	D	F	E	FI	- 1	1	IГ	٦
	ראעו	HΝ			וכ.ו	□. Ͻ	IJ	Е.	г	ГΙ	_ (ш	J

6.7 LITER V-8 DIESEL 400 HP @ 2800 RPM, 800 LBS. FT. @ 1600 RPM BIODIESEL CAPABLE TO 20%

PERMANENT - 40 DEGREES ETHYLENE GLYCOL ANTIFREEZE

6 SPEED ELECTRONIC AUTOMATIC TRANSMISSION

16,500 LBS. GVWR PACKAGE

NO TIRE INFLATION MONITORING SYSTEM

SLIDING REAR WINDOW

HIGH CAPACITY TRAILER TOW PACKAGE

OEM IP MOUNTED ELECTRICAL TRAILER BRAKE CONTROLLER

DEALER APPLIED SUPERIOR RUSTPROOFING

HD ALTERNATOR 200 AMP DUAL 650 CCA MF BATTERIES

VINYL 40/20/40 SEATS FOLDING REAR BENCH SEAT

REAR PRIVACY GLASS

MANUALLY EXTENDABLE TOWING MIRRORS

INTEGRAL 4" X 6" CONVEX MIRRORS

OEM AIR CONDITIONING

MUDFLAPS & SPLASHGUARDS

TRACTION CONTROL & TRAILER ANTI SWAY FITTED

RUNNING BOARDS DEALER FITMENT

HIGH CAPACITY TRAILER TOW PACKAGE

ELOQUIP 9' ALUMINUM DUMP BODY S/N: AAL 12125

ALL 1/8" & 3/16" 5083-H321 ALUMINUM

ALL 1/4" ALUMINUM SHEET MATERIAL 5083-H321 16% MINIMUM 18% MAXIMUM ELONGATION

CROSS MEMBERS 6351-T6 CHANNEL 6" X 2 1/2" X 2 1/2" X 1/8"

LONGSILLS 6351-T6 6" X 2 1/2" X 1/4"

ELECTRO-HYDRAULIC UNDERBODY TIP RAM 45 DEGREE TIP ANGLE

BODY DIMENSIONS 9' LENGTH X 96" WIDTH

BARN DOOR STYLE TAILGATE 18" 3" CHANNEL, 1/8" EXTERIOR & 3/16" INSIDE SKIN

12" HIGH CLEANSIDE DROP DOWN SIDES 6" REMOVABLE BOARDS

SCREENED OPENING BODY FRONT

QUARTER CAB PROTECTOR

VERTICAL STORAGE SLOTS FOR TOOLS

1/4" FLOOR X 2 1/2" ON 12" CENTRES

3/16" FRONT WALL	
BODY PROP SAFETY BAR	

TIE DOWN RAILS ALL AROUND

DRIVER SIDE FRONT LADDER WITH ANTI-SLIP STEPS

TRAFFIC CONE HOLDER CURBISDE REAR

FRONT CURBSIDE FRAME MOUNTED TOOLBOX

BODY FRONT INTERNAL TOOLBOX

TARPAULIN SOLID MESH TYPE

LED LIGHTING

BACK UP ALARM

TWO STROBE FLASHERS AMBER / BLUE CAPABLE 3-POSITION SWITCH FOR PATTERN CHANGE

5" HOIST CYLINDER PTO SWITCH IN IP PANEL SWITCHES 1.3 GPM @ 2700 PSI

HOLLAND PH-30RP41 6,000 LBS. VERTICAL LOAD, 30,000 LBS. GROSS TOW LOAD PINTLE HOOK WITH TOW HOOK EYES

VIBRATOR FITTED