## TOWN UNIT # 344-13 ASSET #: 171359

RECEIVED FROM JOE JOHNSON EQUIPMENT JULY 12,2013

2013 MODEL ODB MODEL LCT-600 SINGLE AXLE TRAILER MOUNTED LEAF

VACUUM S/N: 0513-6205

TRAILER VIN: 1Z9PL1614DR168071

## **VEHICLE IMPORT AUTHORIZATION #: 2274432**

ENGINE 4-CYL TURBO DIESEL JOHN DEERE 4045T F290 IT4

INTERIM TIER 4 EU STAGE 3B S/N:PE4045R902463

WET SLEEVE TYPE, 74 HP @ 2,400 RPM, 195 LBS. FT. @ 1,700 RPM 21% TORQUE RISE @ 1,700 RPM

EXTENDED LIFE COOLANT TO - 40 DEGREES CELSIUS, WITH RECOVERY TANK 600 WATT / 110 VAC BLOCK HEATER

REMOTE OIL DRAIN, HEATED FUEL/WATER SEPARATOR

(151 LITER)40 USG 1/4" WALLS HDPE FUEL TANK ULC/CAN-CSA APPROVED KEYED ON/OFF IGNITION

RADIATOR MESH SCREENS, PRESSURIZED TRASH STYLE, 7 BLADE PULLER FAN ANTI-VANDALISM KIT

SOUND ATTENUATION 85 DBA @ 50 FEET

12 VDC MF 650 CCA BATTERIES, 65 AMP ALTERNATOR, CIRCUIT BREAKERS, 30 AMP RELAY

HD AUTO CLUTCH 13" SINGLE PLATE MODEL:

KEVLAR REINFORCED 4 V POWERBAND VEE BELT 1:1 DRIVE WITH IMPELLOR PTO ENGAGEMENT SMOOTHING DEVICE FITTED

BEARING STATIC RATING 31,920 AND DYNAMIC 27,280 LBS. MINIMUM LIFE 400 HOURS

WITH GREASE LINE EXTENSIONS

TO THE BEARING HOUSINGS USES PREMABLUE EXTREME NLGI1

IMPELLOR HOUSING CLEAN OUT DOOR WITH SAFETY INTERLOCK

32" IMPELLOR W/6 GUSSETED BLADES T1 AR400 STEEL

16" DIAMETER X 3/8 " WALLHOSING

180 DEGREE WORKING RADIUS OF PICKUP HOSE, ELECTRO-HYDRAULIC BOOM FITTED, W/FLOW CONTROL ADJUSTMENT

AXLE RATING 6,000 LBS. TORSION TOR-FLEX 11 SUSPENSION 2,722 KG GAWR ST225-75R15 TIRES 65 PSI/448 KPA 15 X 6 RIMS

12" X 2" ELECTRIC BRAKES WITH CABLE BREAKAWAY FEATURE

48" - 84" TELESCOPING DRAWBAR

2,500 LBS. ELECTRO-HYDRAULIC TONGUE JACK

PLUS MANUAL CRANK HANDLE BULLDOG JACK (1,000 LBS. LIFT & STATIC)

HOSING: SUCTION 16" X 120" EXHAUST 16" X 48" **NOTE BLOWER IS SET AT 40** 

## **DEGREES PER ODB**

BUCHER DYNA JACK MODEL M32190147 S/N: 51103182 0087 RESERVOIR UNIT BUCHER JACK MOTOR MODEL M310-0285 S/N: 50921454 0012 BOTH USE DEXRON ATF