

TOWN UNIT # 347-13 ASSET #: 171362 APPROX. 1,180 HOURS

RECEIVED FROM JOE JOHNSON EQUIPMENT JULY 15,2013

2013 MODEL YEAR ODB LCT-600 SINGLE AXLE TRAILER MOUNTED LEAF VACUUM
S/N: 0513-6208

TRAILER VIN: 1Z9PL161XDR168074

VEHICLE IMPORT AUTHORIZATION # 2274424

ENGINE 4-CYL TURBO DIESEL JOHN DEERE 4045T F290 IT4

INTERIM TIER 4 EU STAGE 3B S/N:PE4045R902474

WET SLEEVE TYPE, 74 HP @ 2,400 RPM, 195 LBS. FT. @ 1,700 RPM 21% TORQUE RISE
@ 1,700 RPM

EXTENDED LIFE COOLANT TO - 40 DEGREES CELSIUS, WITH RECOVERY TANK

600 WATT / 110 VAC BLOCK HEATER

REMOTE OIL DRAIN, HEATED FUEL/WATER SEPARATOR

(151 LITER) 40 USG 1/4" WALLS HDPE FUEL TANK ULC/CAN-CSA APPROVED

KEYED ON/OFF IGNITION

RADIATOR MESH SCREENS, PRESSURIZED TRASH STYLE, 7 BLADE PULLER FAN
ANTI-VANDALISM KIT

SOUND ATTENUATION 85 DBA @ 50 FEET

12 VDC MF 650 CCA BATTERIES, 65 AMP ALTERNATOR, CIRCUIT BREAKERS, 30 AMP
RELAY.

HD AUTO CLUTCH 13" SINGLE PLATE MODEL: XHD 1300 S/N: N/A

KEVLAR REINFORCED 4 V POWERBAND VEE BELT 1:1 DRIVE WITH IMPELLOR
PTO ENGAGEMENT SMOOTHING DEVICE FITTED

BEARING STATIC RATING 31,920 AND DYNAMIC 27,280 LBS. MINIMUM LIFE 400
HOURS

WITH GREASE LINE EXTENSIONS

TO THE BEARING HOUSINGS **USES PREMABLUE EXTREME NLGI1**

IMPELLOR HOUSING CLEAN OUT DOOR WITH SAFETY INTERLOCK

32" IMPELLOR W/6 GUSSETED BLADES T1 AR400 STEEL

16" DIAMETER X 3/8 " WALL HOUSING

180 DEGREE WORKING RADIUS OF PICKUP HOSE

ELECTRO-HYDRAULIC BOOM FITTED, W/FLOW CONTROL ADJUSTMENT

AXLE RATING 6,000 LBS. TORSION TO-FLEX SUSPENSION

ST225-75R15 TIRES 15 X 6 RIMS 65 PSI/448 KPA

12" X 2" ELECTRIC BRAKES WITH CABLE BREAKAWAY FEATURE

48" - 84" TELESCOPING DRAWBAR

2,500 LBS. ELECTRO-HYDRAULIC TONGUE JACK

PLUS MANUAL CRANK HANDLE JACK (1,000 LBS. LIFT & STATIC)

HOSING: SUCTION 16" X 120" EXHAUST 16" X 48"

NOTE BLOWER IS SET AT 40 DEGREES PER ODB BUILD SHEET

BUCHER RESERVOIR MODEL: 32190147 S/N: 511031820072

BUCHER JACK MODEL: M3100285 S/N: 509214540013

BOTH USE DEXRON ATF