

TOWN UNIT #: 349-12 ASSET #: 161133 APPROX: 1,458 HOURS

RECEIVED FROM JOE JOHNSON EQUIPMENT AUGUST 15,2012

2012 YEAR ODB MODEL LCT 600 S/N: 07125996 SINGLE AXLE LEAF VACUUM TRAILER

TRAILER S/N: 1Z9PL1611BR168087

JOHN DEERE DIESEL ENGINE MODEL 4045TF290 **INTERIM TIER 4** S/N: PE4045R872829

BIODIESEL PERMISSIBLE 5%

74 HP @ 2400 RPM, 195 LBS. FT. @ 1700 RPM TORQUE RISE 21% @ 1700 RPM
276 CID, 4.5 LITER

7-BLADE PULLER FAN

HYDRAULIC JACK ASSEMBLY BUCHER HYDRAULICS DYNAJACK MODEL M3100285

HYDRAULIC JACK S/N: 509214540015/G198CC

HYDRAULIC RESERVOIR ASSEMBLY BUCHER HYDRAULICS DYNAJACK MODEL M3290147

HYDRAULIC RESERVOIR S/N: 50981981/G88CC

BLOCK HEATER 110 VAC 600 WATT PLUS GLOW PLUG

ELECTRIC FUEL/WATER SEPARATOR

40 USG 1/4" HDPE FUEL TANK WITH STEEL SURROUND PROTECTION

ANTI-VANDALISM KIT

SOUND LEVEL 85 DBA @ 50'

12 VDC 650 CCA MF BATTERY 40 AMP ALTERNATOR LED STYLE LIGHTING LED STROBE

HD AUTOCLUTCH 13" MODEL XHD1300 DIAMETER SINGLE PLATE DISC

2 1/4" DIAMETER CLUTCH OUTPUT SHAFT

MURPHY AUTO ENGINE SHUTDOWN SYSTEM

KEVLAR REINFORCED 4V POWERBAND DRIVE BELT 1:1 PULLEY/FAN DRIVE RATIO

BEARINGS RATED AT 31,920 LBS. STATIC 27,280 LBS. DYNAMIC 400 HOUR LIFE RATING

LUBE-SITE AUTO FEED GREASE CUPS **USES PERMALUBE EXTREME NLG 1 GREASE**

32" DIAMETER 6-BLADE IMPELLOR 3/8" THICK T-1 STEEL AR 400

16" DIAMETER HOSING INLET & EXHAUST

HYDRAULIC BOOM ASSEMBLY 12 VDC HYDRAULIC PUMP OPERATED

TORFLEX SUSPENSION AXLE 6,000 LBS RATED

TIRES ST225/75R 15 DOT 7YHH 448 KPA 65 PSI 15 X 6 RIMS

12" X 2" ELECTRIC BRAKES, BREAKAWAY CABLE FITTED

ADJUSTABLE TONGUE 48" - 84"

MANUAL SWING AWAY JACK

2,500 LBS. CAPACITY HYDRAULIC JACK WITH CASTOR WHEEL

