

### Stylish and Portable Cooling for Your Large Professional Environment

The all-new Climate Pro K36 brings "roll-it-in, set-it-up and plug-it-in" convenience with the innovative features that distinguish the entire Climate Pro line.

#### Key Features

- Operates on 1 Phase, 208/230V electricity.
- Cools to mid-60s°F — for effective heat control around electronics, servers, and computers.
- Provides 36,000 Btu/h of cool air — maximum spot cooling to just the room that needs it.
- Digital controls and auto operation — allow 24/7 programmable back-up of central systems.
- Effective moisture removal — hastens drying for humid and water-damaged areas.

Another line of quality products by DENSO.

**DENSO**

MovinCool is a brand of DENSO Corporation, the world's largest manufacturer of spot air conditioners. MovinCool spot air conditioners and heat pumps are backed by a full three-year on-site parts and labor warranty with registration — the strongest in the industry.



#### Ideal for . . .

- Offices
- Server and Telecom Rooms
- Hospitals
- Schools
- Laboratories
- Banks
- Emergency Back-up
- Supplemental Cooling
- After-hours Cooling
- Retail Spaces

# MOVINCOOL



## Climate Pro K36 Specifications

		K36
Electronic Features	Control Panel	Programmable
Cooling Capacity	Rating Conditions: 95°F @ 60% RH	36,000 Btu/h
Electrical Characteristics	Voltage Requirement (60 Hz)	1 Phase, 208/230 V
	Total Power Consumption	4.3 kW*
	Current Consumption	19.9 amps*
	Recommended Fuse Size	30 amps
	NEMA Plug Configuration	6-30P
	Min. - Max. Voltage	198 - 253 V
Fans	Motor Output	0.23 kW Evaporator 0.37 kW Condenser
Evaporator	Fan Type	Centrifugal
	Max. Air Flow - High/Mid/Low	920/880/840 CFM
	Max. External Static Pressure	0.6 IWG
Condenser	Fan Type	Centrifugal
	Max. Air Flow - High/Mid/Low	1390/990 CFM
	Max. External Static Pressure	0.5 IWG
Compressor	Type	Hermetic Scroll
	Output	2.3 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	31 x 55 x 53 in
Net Weight/Shipping Weight		454/570 lb
Power Cord	Gauge	12 AWG (3-core)
	Length	6 ft
Condensate Tank Capacity		2 @ 5 gal
Operating Conditions	Min. - Max. @ 50% RH	65° - 95°F
Max. Duct Length	Per Cold Duct Hose	40 ft
	Hot Duct Hose	60 ft
Max. Sound Level	With Condenser Duct - High/Mid/Low	68/67/66 dB(A)
	Without Condenser Duct - High/Mid/Low	70/69/68 dB(A)

\*Specifications information shown with 230 V. All specifications subject to change without notice.

All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit [MovinCool.com/warranty](http://MovinCool.com/warranty) for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

For more information contact:

 **United Rentals**  
Power & HVAC

800-UR-RENTS  
800-877-3687  
[www.unitedrentals.com](http://www.unitedrentals.com)

