

TS400

Versatile & Designed to last

Optoma's TS400 digital projector combines performance and functionality to create the optimal blend of price and performance. Weighing in at 4.4 pounds, the robust and fully featured TS400 is a complete solution for a wide range of applications. From the boardroom to classroom, the TS400 excels!



Features

- **Native 800 x 600 SVGA resolution** for sharp display
- **Bright 2200 lumens** for great image quality for a wide range of applications
- **Superior 2000:1 contrast ratio** for cinema quality images and crisp graphics
- **SXGA+ (1400 x 1050) capability** with high-end laptops
- Fully **HDTV compatible** (720p, 1080i)
- Convenient **Dual D-sub 15 VGA**, component, composite, monitor loop through and S-video input
- Weighs just **4.4 pounds**
- User **password security** locking system
- **Adjustable cooling fan speed** for high altitude usage



Specifications

Brightness

2200 ANSI lumens

Resolution

Native: 800 x 600 SVGA
Max-Resize: 1400 x 1050 SXGA+

Contrast Ratio

2000:1 (Full On/Full Off)

Lamp Life and Type

2,000/3000(ECO) hour
200W UHP lamp

Display Type

0.55-inch DDR DLP™ technology from Texas Instruments

Weight

4.4 pounds (1.9 kg)

Throw Ratio

1.93 - 2.13:1

Image Size (diagonal)

24.6 to 306 inches
(0.6 to 7.77 meters)

Projection Distance

3.9 to 39.3 feet
(1.2 to 12 meters)

Multimedia Audio

2-watt Mono speaker

Compatibility

XGA, SVGA, VGA, VESA, Mac, SXGA+ Resized
NTSC/PAL/SECAM
SDTV (480i), EDTV (480p),
HDTV (720p, 1080i)

Horizontal Scan Rate

15 to 100 kHz

Vertical Refresh Rate

56 to 85 Hz

User Controls

Complete onscreen menu adjustments in 11 languages

I/O Connectors

Dual D-sub15, VGA for monitor loop through, S-Video, composite video, audio minijack, USB (service port)

Power Consumption

265 watts (maximum)
<15 watts (standby mode)

Power Supply

AC Input 100 ~ 240V, auto-switching power supply

Noise Level

28dB

Projection Lens

F= 2.7~3.0, f=21.83~23.81mm,
1:1.2 Manual Zoom and Focus

Dimensions (W x H x D)

9 x 3.7 x 8.26 inches
(230x 95 x 210mm)

Standard Accessories

AC power cord, VGA to VGA, Composite Video, Remote control, Batteries for remote, Lens cap (hanging), Quick start guide, Warranty card and Users guide

Optional Accessories

Ceiling Mount, 15-pin to 3 RCA component/HDTV adapter, S-video cable, Audio out adapter, Universal Remote Mouse kit [USB], Gold Service warranty, Panoview projection screen series

Limited Warranty

3 years limited parts and labor, 90 days on lamp

UPC

796435 11 122 9